



Furtun hidraulic SEL - 4SP SEL
cu patru inserții metalice
DIN EN 856

- strat exterior de cauciuc sintetic rezistent la uleiuri
- patru inserții de oțel spiralat
- strat interior de cauciuc sintetic rezistent la ulei hidraulic
- temperatura de lucru: de la -40°C la +100°C (max.+125°C)

Cod	Inch	Diametru interior (mm)	Diametru exterior (mm)	Presiune de lucru (BAR)	Radius (mm)	kg/m	Preț EUR
4SP 10 SEL	3/8"	9.5	17.5	445	180	0.750	12.33
4SP 12 SEL	1/2"	12.7	20.3	415	230	0.890	13.44
4SP 16 SEL	5/8"	16.0	23.8	350	250	1.070	14.96
4SP 19 SEL	3/4"	19.0	28.2	350	300	1.500	16.47
4SP 25 SEL	1"	25.4	35.1	280	340	1.915	20.75
4SP 32 SEL	1.1/4"	31.8	46.0	210	460	3.050	31.91
4SP 38 SEL	1.1/2"	38.1	52.4	185	560	3.640	42.67
4SP 51 SEL	2"	50.8	65.3	175	660	4.730	64.31

Furtun hidraulic HYPRESS - 4SH HY
cu patru inserții metalice
EN 856 DIN 20023



- strat exterior de cauciuc sintetic rezistent la ulei, uzură și intemperii
- patru inserții de oțel spiralat
- strat interior de cauciuc sintetic rezistent la ulei
- temperatura de lucru: de la -40°C la +100°C

Cod	Inch	Diametru interior (mm)	Diametru exterior (mm)	Presiune de lucru (BAR)	Radius (mm)	kg/m	Preț EUR
4SH 19 HY	3/4"	19.0	32.2	420	280	1.556	22.85
4SH 25 HY	1"	25.4	38.7	380	340	2.087	28.73
4SH 32 HY	1.1/4"	31.8	45.5	325	460	2.571	42.25
4SH 38 HY	1.1/2"	38.1	53.5	290	560	3.439	53.11
4SH 51 HY	2"	50.8	68.1	250	700	4.903	71.09