

| ltem number:<br>EAN:<br>Discount group:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 19 335<br>4103810193354<br>D                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>Technical data</b><br>Length of suction tube (mm):<br>Pressure ratio:<br>Max. diameter (mm):<br>Max. air pressure (bar):<br>Min. air pressure (bar):<br>Recommended air pressure (bar):<br>Cylinder capacity engine (cm <sup>3</sup> ):<br>Cylinder capacity pump (cm <sup>3</sup> ):<br>Quantity of strokes at 8 bar at a free-flow<br>(strokes/min):<br>Pump capacity at 8 bar at a free-flow<br>(l/min):<br>Pump pressure at 8 bar air pressure<br>(bar):<br>Air consumption at 8 bar air pressure<br>(l/min):<br>Length of discharge pipe work:<br>Max. suction heigth:<br>Compressed air connection:<br>Oil connection - suction side:<br>Oil connection - delivery side:<br>Connection container:<br>Noise level idle running acc. to ISO<br>9614-2 at a distance of 2 m (db A):<br>Noise level under load acc. to ISO<br>9614-2 at a distance of 2 m (db A):<br>Viscosity of discharged liquid:<br>Classical liquids to be discharged:<br>Time duration for 1 complete container<br>draining:<br>Lacquering: | 860<br>5:1<br>130<br>8<br>2<br>6<br>220<br>70 |
| Length of engine (mm):<br>Weight of motor (kg):                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 4                                             |

## Specification

- Pneumatic oil pump 5:1, double acting (DW)
- Suction tube, G 3/4" male
- For 200/220 I container

Pneumatic pump 5:1-DW SRL 860-200/220-I-container

- Double-acting pump, provides a continuous flow of media
- Especially designed for oil supply over long distances
- To discharge engine, gear and hydraulic oils
- Designed for use in conjunction with pipe lines. We strongly recommend the use of an overflow valve ((19 648), 16 bar, or (19 506), 20 bar).
- Can be easily combined with several hose reels

## **Special notes**

• Operate pneumatic pump with maintenance unit (20 218 950)

## Packaging

Dimensions LxWxH (mm): Weight (kg): Packing unit: 1310 x 190 x 195 7,42 1,0