



## Rotary pump

SRL 355-955 mm-18 l/min

**Item number:** 13 055  
**EAN:** 4103810130557  
**Discount group:** A

### Technical data

Delivery rate (l/rotation):	0,3
Delivery rate at 60 rotations/min; pumping medium diesel (l/min):	18
Pumping media:	self-lubricating and non-aggressive media: fuel oil, diesel, petroleum, coolant fluid (undiluted); machine maintenance: hydraulic oil, cutting fluid, gear oil, oils up to SAE 90
Usage:	container for 60 / 200 / 220 l
Application:	for filling measuring vessels, storage cans, canisters and machines
Discharge:	discharge spout
Length, three-part suction pipe (mm):	355 - 955
Barrel screw coupling:	G 2" male
Material pump housing:	impact-resistant zinc die casting ZL 410
Colour crank:	silver
Colour gear cover and gear housing:	blue
Colour housing:	blue
Weight (kg):	2,371

### Specification

- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- With suction filter (13 097 003)
- Barrel screw coupling G 2" (04 464 001)
- Discharge spout (81 112)

### Special notes

- Smooth hand-rotating operation
- The pump is continuously positionable in 360°
- Telescopic suction tube variable from 355 mm to 955 mm
- Assembly, commissioning and container change without tools
- CNC machined, thus optimum pump efficiency
- Impact resistant pump housing
- Covering of the different components exclusively through the seals
- Completely dismountable - easy to clean
- Spare parts available for 10 years
- Available in 4 colour variants
- Variations: discharge hose 2 m (13 056); discharge hose 2 m and meter (13 057)
- Warranty 3 years when using the supplied suction basket (excluding wear parts)

### Packaging

Dimensions LxWxH (mm):	390 x 245 x 125
Weight including package (kg):	2,838
Packing unit:	1,0

